

Larsen Building Products Ltd

SLC Plus



Professional SLC 1500 Commercial

By Larsen Building Products Ltd

Detailed description

Fast drying, hand or pump applied cement based underlayment. Manufactured from a controlled blend of special sands, cements and synthetic polymers to give a high quality flooring product which is self-levelling and smoothing. For use in fast track domestic and commercial situations such as where levelling of up to 25 mm is required or when finishes need to be applied quickly. It is ideal for offices, dwellings, schools, hospitals, airports etc, and is suitable for use over underfloor heating, but is not a wearing surface. SLC 1500 must be overlaid with a suitable resilient floor finish, carpet, ceramic tiles, vinyl, resin coatings etc.

Product guidance - As Standard

Features:

- Form: Granular.
- Aggregate size (maximum): 0.6 mm.
- Bed thickness (maximum): 25 mm.
- Mix: 25 kg powder:5 L water.
- Application temperature: + 5–30°C.
- Light traffic: 2–4 hours.
- Full traffic: 1–2 days.
- Coverage: 1 m² per 25 kg @ 12.5 mm.
- Screed compressive strength: 30 MPa.
- Single pack.
- Self levelling.

Product specification

Manufacturer

- Name: Larsen Building Products Ltd
- Web: www.larsenbuildingproducts.com
- Email: joris@larsenbuildingproducts.com

Product reference

Professional SLC 1500 Commercial

Primer

Not required

Larsen acrylic primer diluted 1:1 with clean water - Normal concrete/ screed.

Larsen acrylic primer diluted 1:1 with clean water followed by a coat of neat acrylic primer - Particularly porous concrete/ screed.