

Larsen Building Products Ltd

NS Plus



Professional SLC 1900 Base

By Larsen Building Products Ltd

Detailed description

Fast drying, hand or pump applied cement based levelling screed to level thicker sections economically. Manufactured from a controlled blend of special sands, cements and synthetic polymers to give a high quality flooring product which is self-levelling and smoothing. Suitable for use in fast track commercial and industrial situations.

Product guidance - As Standard

Features:

- Form: Granular.
- Colour: Grey.
- Aggregate size (maximum): 3.0 mm.
- Bed thickness: 5–50 mm.
- Mix: 25 kg powder: 4.5–5 L water.
- Application temperature: + 5–30°C.
- Light traffic: 2–4 hours.
- Full traffic: 1–2 days.
- Coverage: 1.25 m² per 25 kg @ 10 mm.
- Screed compressive strength: 25 MPa.
- Single pack.
- Self levelling.

Product specification

Manufacturer

- Name: Larsen Building Products Ltd
- Web: www.larsenbuildingproducts.com
- Email: joris@larsenbuildingproducts.com

Product reference Professional SLC 1900 Base

Primer Not required
Larprime EU primer - Heavy traffic areas.
Larsen acrylic primer diluted 1:1 with clean water - Normal concrete/ screed.
Larsen acrylic primer diluted 1:1 with clean water followed by a coat of neat acrylic primer - Particularly porous concrete/ screed.

