

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

Trade Fast Set Flex

Revision 5

Revision date 2017-08-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Trade Fast Set Flex
---------------------	---------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC1] Adhesives, sealants; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

Intended use


	This product is intended for use as an adhesive for ceramic (or similar) tiles.
--	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/37/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes, respiratory system and skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; Acute Tox. 4: H332; STOT SE 3: H335; STOT RE 2: H373;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage.

Trade Fast Set Flex

Revision 5

Revision date 2017-08-30

2.2. Label elements

Precautionary Statement: Prevention	Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary Statement: Disposal	P405 - Store locked up. P501 - Dispose of contents/container to

Further information

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4				
Portland Cement		65997-15-1	266-043-4			Xi; R36/37/38	
Calcium Sulphate		7778-18-9	231-900-3			Xi; R36/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4			Acute Tox. 4: H332; STOT RE 2: H373;	
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;	
Calcium Sulphate		7778-18-9	231-900-3				

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated

Trade Fast Set Flex

Revision 5

Revision date 2017-08-30

4.1. Description of first aid measures

Ingestion	clothing. Seek medical attention if irritation or symptoms persist.
	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values


Trade Fast Set Flex

Revision 5
Revision date 2017-08-30

8.1.1. Exposure Limit Values

Calcium Sulphate	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: WEL 15 min limit mg/m3: WEL 15 min limit mg/m3 total inhalable dust: WEL 15 min limit mg/m3 total respirable dust:
Portland Cement	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: 0.1 WEL 15 min limit mg/m3: WEL 15 min limit mg/m3 total inhalable dust: WEL 15 min limit mg/m3 total respirable dust:

8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Suitable eye protection.
Skin protection - Handprotection	Wear suitable gloves.
Skin protection - Other	After contact with skin, wash immediately with plenty of water.
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment. Suitable half mask respirator with filter P2 (EN 143). Suitable half mask respirator with filter P3 (EN 143).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey/White
Solubility	Slightly miscible in water

SECTION 10: Stability and reactivity

10.1. Reactivity

	Avoid contact with: Strong acids. Avoid contact with: Strong bases.
--	---

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Organic materials.
--	--------------------

10.4. Conditions to avoid

--	--

Trade Fast Set Flex

Revision 5

Revision date 2017-08-30

10.4. Conditions to avoid

Heat, sparks and open flames.

Further information

Avoid formation of dust.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Serious eye damage/irritation

Acute effect.

Respiratory or skin sensitisation

May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Further information

No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations. European Waste Catalogue: 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.

Disposal methods

Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 14: Transport information

14.1. UN number

The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

14.4. Packing group

The product is not classified as dangerous for carriage.

14.5. Environmental hazards

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

Trade Fast Set Flex

Revision 5

Revision date 2017-08-30

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	R36/37/38 - Irritating to eyes, respiratory system and skin. R36/38 - Irritating to eyes and skin.
Text of Hazard Statements in Section 3	Acute Tox. 4: H332 - Harmful if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--